



POWER

Engine	Four-stroke, liquid-cooled, DOHC, four valves per cylinder, parallel twin
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression ratio	10.8:1
Fuel System	DFI® with two 38mm throttle bodies, with sub-throttles
Ignition	TCBI with digital advance
Transmission	Six-speed with positive neutral finder
Final Drive	Sealed chain

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork / 5.1 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload / 3.2 in
Front Tire	120/70x18
Rear Tire	160/60x17
Front Brakes	Single 300mm disc with twin-piston caliper and ABS
Rear Brakes	Single 250mm disc with single-piston caliper and ABS
Cooling System	Liquid

DETAILS

Frame Type	High-tensile steel double pipe perimeter frame
Rake/Trail	31 degrees / 4.7 in
Overall Length	91.0 in
Overall Width	34.7 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	498.3 lb**
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Color Choices	Candy Lime Green, Pearl Crystal White, Flat Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).